

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **08219920 A**

(43) Date of publication of application: **30.08.96**

(51) Int. Cl.

G01L 17/00
B60C 23/00
G01H 3/08

(21) Application number: **07021723**

(22) Date of filing: **09.02.95**

(71) Applicant: **NIPPON SOKEN**
INC/NIPPONDENSO CO LTD

(72) Inventor: **HAYASHI IKUO**
NISHIKAWA YOSHIHIRO
SUZUKI MOTOJI

(54) PNEUMATIC PRESSURE DETECTOR FOR TIRE

(57) Abstract:

PURPOSE: To detect the pneumatic pressure of a tire even when there is environmental variation by extracting a resonance frequency in a frequency range selected by means for selecting a frequency range depending on the vehicle speed.

CONSTITUTION: Each tire 1a-1d of a vehicle is provided, respectively, with a wheel speed sensor 2-5. Each sensor 2-5 comprises a gear 2a-5a and a pickup coil 2b-5b. The gear 2a-5a is fixed coaxially with the rotary shaft of each tire 1a-1d and made of a magnetic disc. The coil 2b-5b outputs an AC signal having a period in response to the rotational speed of the tire 1a-1d. AC signal outputted from the coil 2b-5b is fed to a microcomputer comprising CPU, ROM and RAM and an electronic controller 6 comprising a shaper circuit and predetermined signal processing is carried out including the shaping. Results of signal processing are delivered to a display section 7.

COPYRIGHT: (C)1996,JPO

